

# HENAN QIFAN ELECTRIC CO.,LTD

No.903,Guohong building, Huagong Road,High-tech Area ,Zhengzhou,China

Mob: 0086 13643808550

Email:steven@hnqifancable.com

## Technical Parameter for 12/20KV NA2XSOH 1x95mm<sup>2</sup>

Item	Description	Unit	Parameter
1	Reference standard	--	IEC60502-2, IEC60228
2	Rated voltage	KV	12/20(24)
3	<b>Conductor</b>		
	Conductor Material	--	Stranded aluminum wire compact round
	Core number of conductor	--	1
	Conductor cross-sectional area	mm <sup>2</sup>	95
	Min. stranding number	Nos	15
	Approx. conductor diameter	mm	11.0--12.0
4	<b>Conductor screen</b>		
	Material of conductor screen	--	Semi-conducting compound
	Nominal thickness of conductor screen	mm	0.7
5	<b>Insulation</b>		
	Insulation material	--	XLPE
	Nominal thickness of insulation	mm	5.5
6	<b>Insulation screen</b>		
	Material of insulation screen	--	Semi-conducting compound
	Nominal thickness of insulation screen	mm	0.7
7	<b>Metal screen (Lapping with overlap)</b>		
	Screen material	--	Aluminum tape
	Minimum thickness	mm	0.3
8	<b>Wrapping tape</b>		
	Non-woven wrapping tape	mm	0.2
9	<b>Outer sheath</b>		
	Material of outer sheath	--	Flame retardant low smoke zero halogen (LSZH)
	Nominal thickness of outer sheath	mm	1.9
	Approx. diameter over outer sheath	mm	30.9
10	Approx. weight of cable	Kg/km	1022
11	Max. D.C. Resistance of conductor at 20°C	Ω/km	0.320

# HENAN QIFAN ELECTRIC CO.,LTD

No.903,Guohong building, Huagong Road,High-tech Area ,Zhengzhou,China  
 Mob: 0086 13643808550      Email:steven@hnqifancable.com

Item	Description	Unit	Parameter
12	A.C resistance of conductor at 90°C	Ω/km	0.4106
13	A.C high voltage test at 42KV, 5minutes	--	No breakdown
14	Inductance	H/m	$3.901 \times 10^{-7}$
15	Reactance at 50Hz	Ω/km	0.123
16	Capacitance	μF/km	0.227
17	Charging current	A/km	0.85
18	Short circuit rating of conductor	KA/1sec	9.0
19	<b>Current rating</b>		
	In air temperature 40°C	A	245
	In ground temperature 25°C Thermal resistivity of soil 1.5K.m/W Depth of laying 0.8m	A	260

